

Marine Wall Mount Brackets

SKU 32-0501

To be used with Marine Grade Deluxe Wall Mount Racks

Updated October 2011

Suspenz, Inc. Spacing Chart ©

Boat Length	Ideal Tower Spacing (40%)	Min/Max spacing for each kayak (35% / 50%)
8'	3' 2"	2' 10" / 4'
8' 6"	3' 5"	3' / 4' 3"
9'	3' 7"	3' 2" / 4' 6"
9' 6"	3' 10"	3' 4" / 4' 9"
10'	4'	3' 6" / 5'
10' 6"	4' 2"	3' 8" / 5' 3"
11'	4' 5"	3' 10" / 5' 6"
11' 6"	4' 7"	4' / 5' 9"
12'	4' 10"	4' 2" / 6'
12' 6"	5'	4' 5" / 6' 3"
13'	5' 2"	4' 7" / 6' 6"
13' 6"	5' 5"	4' 9" / 6' 9"
14'	5' 7"	4' 11" / 7'
14' 6"	5' 10"	5' 1" / 7' 3"
15'	6'	5' 3" / 7' 6"
15' 6"	6' 2"	5' 5" / 7' 9"
16'	6' 5"	5' 7" / 8'
16' 6"	6' 7"	5' 9" / 8' 3"
17'	6' 10"	5' 11" / 8' 6"
17' 6"	7'	6' 2" / 8' 9"
18'	7' 2"	6' 4" / 9'
18' 6"	7' 5"	6' 6" / 9' 3"
19'	7' 7"	6' 8" / 9' 6"
19' 6"	7' 10"	6' 10" / 9' 9"
20'	8'	7' / 10'
20' 6"	8' 2"	7' 2" / 10' 3"
21'	8' 5"	7' 4" / 10' 6"
21' 6"	8' 7"	7' 6" / 10' 9"
22'	8' 10"	7' 8" / 11'
22' 6"	9'	7' 11" / 11' 3"



Item #	Parts List	Qty
1	Yellow Wall Mount Bracket	2
2	Stainless Steel Phillips Head Screw	4
3	Stainless Steel Flat Washer	4

Tools required:

1. Measuring tape
2. Pencil to mark the hole positions
3. Electric drill to set the pilot holes
4. 3/16" Drill bit to set the pilot holes
5. Phillips Head screwdriver
6. Bar of soap

Mounting of Rack:

1. Use the Spacing Chart above to determine the distance between Wall Mount Rack brackets.
2. Rub soap on the screw threads for ease of installation.

NOTE: Be sure to mount the Mounting Brackets into a stud. *Screwing only into drywall is not sufficient and could result in injury to self and kayak.*

Guarantee

All Suspenz products are guaranteed for one year for materials and workmanship. The guarantee is affective to the original owner and if the product was cared for and used in the manner it was intended. Contact Suspenz directly with any questions.

www.suspenz.com



Suspenz Inc.
 8725 Roswell Road #0-220
 Atlanta GA 30350
 770-518-0045

KAYAK-CANOE
Storage racks

Suspenz™