

# **Naked Rack**



Surfboard | Wakeboard | Snowboard | Skateboard | Paddleboard

## THANK YOU FOR YOUR PURCHASE!

Please read all instructions before installing this product

#### **SAFETY INSTRUCTIONS & PRODUCT WARNINGS**

Installation circumstances vary by customer so please use common sense and caution when installing this product. StoreYourBoard, a Spire LLC company, is not responsible for hazards or damages related to installation and use, including improper or inadequate mounting. Make sure to wear eye protection during installation and check for electrical wiring inside the wall before screwing or drilling into the wall. **Not suitable for children.** 

#### WHAT'S INCLUDED

- 2 Rack Arms
- 4 Mounting Screws
- 4 Drywall Anchors (Not for Naked SUP)

### **WHAT YOU NEED**

- Phillips Screw Driver
- Tape Measure / Ruler
- Pencil
- Stud Finder / Nail & Hammer
- Level (optional)

#### **MOUNTING INSTRUCTIONS**

- 1. Decide where you want to mount your Naked Rack. For optimal board support, anchor the Naked Rack to wall studs. To locate studs use a stud finder or nail and hammer. As an alternative, you can use the provided drywall anchors. Board weight is limited to 30 pounds if using drywall anchors. \*Drywall anchors are NOT provided for the Naked SUP, which must be mounted to wall studs or a substantial mounting surface to support your SUP.
- 2. Place the Naked Rack against the mounting surface in its desired location. Use a pencil to mark on your wall the 2 mounting holes on the Naked Rack.

For Wall Studs: Secure the Naked Rack into the wall using the provided mounting screws.

<u>For Drywall Anchors:</u> Drywall anchors may break if screwed into a stud or other obstruction behind the wall. First test your mounting location for obstructions using a screw. Then, screw the drywall anchor into the wall with a #3 phillips head screw driver until the flat front of the anchor is flush with the drywall. Do this for both mounting holes you marked. Next, place the Naked Rack against the wall and line up the rack's mounting holes with the drywall anchors. Insert screws through the rack and into the drywall anchors and tighten.

- **3.** Repeat Step 2 to mount the second rack arm. Use the board you plan to store in the Naked Rack to determine how far apart to mount the arms. Use a level or measure up from the floor to make sure the rack arms are level.
- 4. Test both rack arms of the Naked Rack: apply gentle pressure with your hand to make sure the rack is anchored securely.
- 5. Store and display your board in the Naked Rack!

For more details on installation and mounting tips visit: http://www.storeyourboard.com/mounting-and-installation-guide/





