



# SUP Stash

by  StoreYourBoard.com™

## THANK YOU FOR YOUR PURCHASE!

Please read all instructions before installing this product

### SAFETY INSTRUCTIONS & PRODUCT WARNINGS

It is the user's responsibility to ensure the safe and proper use of this product. StoreYourBoard, a Spire LLC company, is not responsible for damages or injuries related to installation or use, including improper or inadequate mounting. Wear eye protection during installation and check for electrical wiring in the wall before screwing or drilling into the wall. **Not a toy; not intended for children. Misuse of this product could result in serious injury or death.**

#### WHAT'S INCLUDED

- 2 - Rack Arms
- 8 - Plastic Mounting Brackets
- 8 - Mounting Screws
- 4 - Plastic Drywall Anchors

#### WHAT YOU NEED

- Drill & 1/4" Drill Bit
- Phillips Screw Driver
- Tape Measure or Ruler
- Pencil
- Stud Finder or Nail and Hammer

#### SPACING

The SUP Stash consists of 2 arms that can be mounted at any desired distance to fit the length of your paddleboard. As a general recommendation, space the arms apart at a distance of 40% of the length of your paddleboard. This will help evenly distribute the weight of your board on the SUP Stash.

#### MOUNTING INSTRUCTIONS

**1. Locate Studs.** Decide where to mount your SUP Stash and locate the closest studs. You must mount at least one screw from each mounting bracket into a stud (see diagram at lower right). Use a Stud Finder or Nail and Hammer to locate your wall studs, which are typically spaced 16" apart.

**2. Mark Mounting Points.** Each rack arm is secured to the wall with 2 sets of mounting bracket pairs: a front and back bracket encircles the rack at both the top and bottom of the rack arm. Mount one of the mounting brackets below the base of the SUP supporting arm and mount the other at the break in the foam mid-way up the arm (see diagram at upper right). Place the mounting bracket and mark the holes. Typically one hole will be on the stud and the other will require a plastic drywall mounting bracket (see diagram at lower right).

**3. Mount First Rack Arm to Wall.** Start with the bottom mounting brackets. Insert screw through both pieces of the mounting bracket pair and loosely screw into the stud. Confirm location of the second mounting hole; if it does not hit the stud you must use a plastic drywall anchor. Drill a 1/4" hole in your drywall and then insert the plastic mounting anchor. Insert the rack through the hole in the center of the mounting brackets. Insert screw into other side of mounting bracket and tighten. Return to tighten the first screw completely. Repeat the process for the top mounting bracket.

**4. Mount Second Rack Arm to Wall.** Repeat mounting process for second rack arm. Mount at the same height to ensure your board is stored level. After both arms are secured to the wall, apply pressure with your hand to ensure the rack is mounted securely.

#### USE INSTRUCTIONS

**1. Weight Limit.** The weight limit of the SUP Stash is 50 pounds.

**2. Features.** The SUP Stash folds against the wall when not in use. The bottom hook is perfect to store your paddle, PFD, leash, and any other SUP gear.

